

SILK GlamArt METALLICA



Drying Time



Surface dry: 1 hour
Hard dry: 6-8 hours

Dilution Ratio



200 ml water/1 litre of Metallica for roller/brush application.
No dilution for design application

Shelf Life



Up to 36 months from the date of manufacture

Coverage



Direct application: 130-150 sq. ft./ltr./coat*

*Coverage may vary due to factors such as application methods, nature of substrate, conditions etc.

Product Description

Silk GlamArt Metallica is a premium water based product. It is 100% acrylic emulsion paint for interior/exterior application. This special effect paint gives glossy metallic finish for various applications such as wall, wood, metal etc.

Usage Areas

Interior and Exterior/POP/puttied/wooden/metal surfaces

Directions for Application



On Previously Painted Surfaces:

Strip the old paint and all the loose particles from the surface and wipe down. Sand it with emery paper 80/100 and wipe clean.

Apply the first coat of primer and let it dry for 6 to 8 hours.

Smoothen the surface by applying thin coats of Happy wall putty (No dilution) to fill in all the dents. Let the putty to dry overnight.

Sand the surface again, with emery paper 200/220, and wipe clean. Apply the second coat of primer and let it dry for 6 to 8 hours. Sand the surface with emery paper 320 and wipe clean.

Apply one coat of illusions Sealer and allow it to dry for 6 hours.



On Fresh/New Surfaces:

Strip all the loose particles from the plasterd surface through wire brushing and scraping and wipe down before starting the above process.



Direction for Application in wooden/ Metal surfaces:

Wooden surfaces should be primed with wood primer. Metal surfaces should be primed with Red Oxide/ Zinc Chromate primer.



Points To Note:

- Stir well and strain before use.
- Do not apply when ambient temperature is below 10°C.
- Recoat and drying of paint are tested at 30±2°C and 60-65% RH. These may vary under different conditions.
- Fire Hazard Class: Non-Flammable.
- Tint with Berger Paints colorants only to get desired shade from Berger Shade card.
- Keep the container tightly closed in cool and dry place.
- Please keep it out of reach of children and away from foodstuff.
- In case of contact with eyes, wash immediately with water and seek medical advice.
- For safety measures, refer to MSDS.

Version No: BPP1/01/2024. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com