

LUXOL WOOD VARNISH

LUXOL WOOD VARNISH



Product description

- It is a one component Glossy clear system specially designed for Natural Wood & Wood Veneer.
- It is available only as a high gloss product categorically meant for Interior Wood.

Performance benefits:

- A specially designed Varnish having finest clarity and gloss giving a wet look finish.
- It has a long-lasting sustainable gloss and holds value for money.
- Very easy to apply – doesn't need Spray Gun like 2k or 3k products. Can be applied by brush or cloth.
- No added lead, mercury and chromium.

Recommended use:

Applicable for interior finishing of furniture's, wooden crafts, MDF boards, veneers, plywood etc. Can be used as a top coat over NC Sanding Sealer or can be used as a multi-coat with the product itself acting as base-coat as well as top coat. Limited to Interior use only.

WHY 1K PU IS BETTER THAN CLEAR VARNISH

- a. 1k PU can be used on exterior wood/Clear Varnish can only be used in interior wood.
- b. 1k PU available in both Matt & Gloss/Clear Varnish is available only in Gloss.
- c. 1k PU is having faster drying time than Clear Varnish.
- d. 1k PU is available in Clears as well as in Oak Yellow shade/Clear varnish available only in clear version.
- e. Having PU in the product recipe – hence better durability/higher gloss with better gloss retention than Clear Varnish.

TECHNICAL DATA

	Glossy Clear
Viscosity in Sec, FCB4 Cup	75 ± 5
Specific Gravity, gm/Lt	0.90 ± 0.01
Coverage Sq. Meter/ltr/Coat at 30 Micron DFT	15-16
% Thinner Intake	5-10
Gloss Values, at 20°	76 minutes
Surface Dry	6 Hours.
Hard Drying	Overnight
Shelf Life in months for the originally packed tightly closed condition maintained at 25° C	24