



WEATHERCOAT LONG LIFE 7

LUXURY EXTERIOR EMULSION WITH SILICON



Product Attributes



Truly durable

Excellent film integrity that provides seven year performance warranty

Water repellent

Silicon additives provide excellent water repellence and protection against rain



Dirt pick-up resistance

Unique polymer composition prevents dust settling on the exterior walls and keep walls looking fresh

No black streaks

Preventing dust settling on the walls also prevent the appearance of black streak marks after rain



Advanced Anti-fungal & anti-algae protection

Prevents fungal and algal growth on exterior walls and is ideal for heavy rainfall areas.

High sheen

High sheen finish on the exterior walls increases the curb appeal of your house



Green Pro Certified

Validates our effort in striving towards cleaner, more sustainable future.

Product Description

WeatherCoat Long Life 7 is a high- performance, premium acrylic exterior emulsion with unique chemical composition that protects your wall from the damaging effects of harsh weather conditions. The paint has great water-repellent property, in addition to its polymer composition that prevents dust settling on the walls. The paint also comes with a 7-year warranty and retains a newly painted look for years.

Recommended Use

Exterior plastered surfaces, asbestos, concrete blocks, fiberboards

Colour Range



Over 2,000 shades

Finish



High sheen

Toxicity



VOC - 38.4 gm/lt

Coverage

65-70 sq.ft/lt/2 coats, under ideal test conditions.
(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: For wall/ plastered surfaces – WeatherCoat Exterior Primer / Alternatively, WeatherCoat All Guard diluted using 1 L of water with 1 L of emulsion may be used

Putty: For wall/plastered surfaces – Bison Wall Putty

Recommended Surface

Sand/ cement plaster, asbestos, brickwork, concrete block and fiberboard

Drying Time



SD: 60 min depending on weather conditions
HD: 6 - 8 hours

Gloss Level



10 - 15 at 60° GH when released

Application Method



Brush / Roller / Spray

Recommended Thinner



Potable water

Dilution Ratio



Brush: 350 ml of water/1L emulsion
In case of N Base shades, no dilution is advised to ensure proper colour depth.

Dilution of dark shades only



Maximum dilution should be 10 - 15 % depending on shade. Coverage may be less compared to light shades.



WEATHERCOAT LONG LIFE 7

LUXURY EXTERIOR EMULSION WITH SILICON



Packs



ColorBank/ Non-ColorBank – Pack
0.9, 1, 3.6, 4, 9, 10 and 20 L
Note: 18 L for N and N1 bases only

Bases

PO, W1, N, N1, Cream and Yellow



Fire Hazard Class
Non-flammable



Pot Life of Thinned Material
Overnight

Surface Preparation



For fresh/new surfaces: Strip all loose particles from the surface with wire brushing and by scraping, followed by a wipe down. Wash the surface down with water and allow it to dry.



Apply one coat of primer and allow it to dry for 6 – 8 hours.

For Previously Painted Surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ Do not apply paint on lime washed surfaces and damp wall
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/03/2020. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com